



VESA installation standard :100*100mm

17" Display

J1900
processor

2GB DDR3
32GB SSD

Aluminum Case

Compact fanless

IP 65

Multi OS

Introduction

PPC-3170B is a newly developed 17-inch HD Industrial Tablet PC, based on Intel® Celeron J1900 2.0GHz processor, comes standard with 2GB DDR3L memory, supports single channel 1600/ 1333MHz DDR3L / 1.35V memory, maximum support 8GB. Support 2* SATA hard disk interfaces, 1* Gigabit Ethernet port, 4* USB interfaces and 6* COM serial ports, support SIM card slot and Mini-PCIE 3G / WiFi modules, rich hardware and software resources could meet a variety of industrial applications. PPC-3170B industrial tablet PC is widely used in any systems related human-machine interfaces (HMI) and displays, such as industrial control terminal, embedded terminal, self-service refueling machine, self-service vending machine, POS machine, ATM, self-service library and other applications of self-service terminal equipment. At the same time, we can customize and develop various types of Tablet PCs according to your needs, including hardware platform based on ARM architecture, increase hardware equipment, increase the interfaces as well as customize the appearance structure.

Features

- ◆ 17" TFT SXGA LCD HD Panel, Resolution 1280*1024
- ◆ Based on Intel® Celeron J1900 2.0GHz Processor, quad core four threads
- ◆ Standard 2GB DDR3L Memory and 32GB SSD Storage
- ◆ Support LVDS、VGA、HDMI Display Interfaces, Support Synchronous/Asynchronous display
- ◆ Reinforced aluminum case, compact fanless design
- ◆ Support 1 *Gigabit Ethernet, 6 *COM ports, built-in 2 *SATA Interfaces and 1 Mini-PCIE
- ◆ Support WIN7/WIN8/WIN10、Unix/Linux Operating System
- ◆ Customize Intel Bay Trail-I/M/D All Series CPU for Flexible Selection

Specifications

Model	PPC-3170B
Screen Size	17-inch TFT LCD
Resolution	1280*1024
Brightness	350cd/m ²
Contrast	1000 : 1
Screen Grade	Industrial Level
Touch Screen	Resistive Screen
CPU	Intel Celeron J1900 2.0GHz, optional J1800/2Cores/2.41GHz processor
Chip	Based on Intel Bay Trail SOC, Compatible Intel Bay Trail-I/M/D all series CPU
Memory	Standard 2GByte DDR3L, support single channel 1600/1333MHz DDR3L/1.35V memory, max support 8GB
Hard Disk	Standard 32GByte SSD
BIOS	64MB FLASH ROM
Storage	1*2.5" SATA (can install hard disk directly) 1*mSATA slot, transmission speed up to 3Gbps
Display	Integrated Intel HD Graphics Core GPU, 1*VGA、1*HDMI、1*LVDS (support Dual channels 24Byte)、support HDMI、VGA、LVDS Synchronous/Asynchronous display
LAN	1*10/100/1000Mbps adjustable

Serial	6
USB	3*USB2.0 480Mb/s , 1*USB3.0 5Gb/s
Audio	Realtek HD ALC662, 6-channel Hi-Fi Audio controller support MIC/Line-out, support 5w/2Ω speaker
PCIE	1*standard Mini-PCIE interface, support 3G、WiFi module
Switch	1*Power Switch
Power Input	DC12V
Power	21W
Chassis material	Aluminum
Front panel	IP65 Standard
Watch Dog	256 Levels 0-255s (support Hardware reset)
Oper Tem.	Tem: 0~50°C Hum: 10%~90%RH@31°C, no condensation
Environ Tem.	Tem: -20~60°C Hum:10%~95%RH@39°C no condensation
System	Microsoft Windows 7/8/10、Linux/Unix
Weight	6.8KG
Mounting Method	Embedded or wall hanging panel (VESA installation standard : 100*100mm)

Size

